



DOE's EGS Program Review

Prediction and Control of Attributes of Induced Fractures in EGS

Jeff Roberts and Russ Detwiler

LLNL

925-422-7108/925-423-1057

jjr@llnl.gov

July 18, 2006

Marriott Hotel
Golden, CO



Project Objective

- Maintaining or increasing fracture permeability is critical to effective EGS implementation.
- Mechanisms that lead to alterations of fracture permeability include:
 - Mechanical deformation
 - Geochemical alteration
 - Thermal stress

Initial objectives

Added objective
- We are integrating laboratory experiments and model development lead to:
 - Improve understanding of coupled processes in fractured rocks under reservoir conditions
 - Develop scalable tools for predicting the impact of coupled processes on fracture permeability evolution




EGS Problem

- Effective operation of EGS reservoirs requires improved tools for predicting the effect of coupled chemical / mechanical / thermal stresses on the long term evolution of fracture permeabilities.
- Such tools can directly aid in:
 - Development of operation plans to extend a well's lifetime
 - Maximizing net thermal output by maintaining / increasing fracture surface area.
 - Assessing the potential for developing / maintaining adequate fracture permeability in prospective EGS formations.
- Development of effective computational tools requires experimental data to test the models.
- We measure permeability evolution in EGS rocks at reservoir conditions under carefully controlled conditions to:
 - 1) determine how the physical and chemical properties of rocks and fluids control the permeability evolution of induced fractures in geothermal fields;
 - 2) suggest optimal strategies for sustaining permeability; and
 - 3) apply this knowledge in support of DOE EGS field experiments.
- Efforts support the Desert Peak East EGS project and include direct collaboration with ORMAT and GeothermEx.
- Because the conceptual and numerical models developed explicitly incorporate the relevant mechanisms, they are applicable to any EGS effort provided adequate knowledge of the rock and fluid properties.



Background/Approach

Integrated experimental/computational study to develop enhanced models of mechanisms that alter fracture transmissivity in EGS Systems




July 18, 2006


Marriott Hotel
Golden, CO



Background/Approach



- Quartz Monzonite major mineralogy:
 - Plagioclase 44%
 - Potassium feldspar 23%
 - Quartz 7%
 - Mica 3%
- Planar fractures with one roughened surface:
 - Reproducible aperture field statistics
 - Realistic surface mineralogy
 - Insensitive to small registration errors when reconstructing aperture fields from surface measurements








Background/Approach

Fracture surfaces analyzed before and after flow experiments using:


Surface profilometry



x-y resolution: $30\text{ }\mu\text{m}$,
z resolution: $5\text{ }\mu\text{m}$



SEM




SEM images provide detailed measurement of surface characteristics / mineralogy

Surface profiles allow reconstruction of initial / final fracture aperture fields for input into models




Background/Approach



- Experiments to date use two fluids with different Si-saturation states:
 - Far-from-SiO₂ saturation fluid (Na, Cl) - e.g., near injection well
 - Near SiO₂ saturation fluid (Na, Ca, K, Cl, SiO₂) - e.g., far from injection well
- Flow experiments approximate reservoir conditions:
 - Temperature: 167 C
 - Confining pressure: 800 psi (5.52 MPa)
 - Pore pressure: 250 psi (1.73 MPa)





Results/Accomplishments



- Long term flow experiments at reservoir pressure / temperature:
 - Far-from-SiO₂ saturation fluid
 - Rock surfaces experience net dissolution
 - Slow decrease in b_{eff} may be due to dissolution of contacts between surfaces
 - Near SiO₂ saturation fluid
 - Surfaces experience net precipitation
 - This leads to a much faster reduction in b_{eff}

Results/Accomplishments



- Far-from-saturation-injectate
 - 65 days @ 0.02 – 0.01 mL/min removed ~20 m
- Near-saturation-injectate
 - 37 days @ 0.02 mL/min added ~4 m

- Batch geochemical model overestimates change in fracture aperture for both cases.
- May be due to localized variability due to
 - Flow channeling
 - Mineral heterogeneity





Results/Accomplishments

Before



After

42 mm



- Measured aperture fields (far from saturation):
 - Aperture growth localized near inflow not uniform over surfaces
 - Significant dissolution along cemented cross-cutting fracture
 - Mean aperture $\sim 30 \mu\text{m}$ ($\sim 40\%$) larger after flow, agreeing with geochemical model
- SEM images:
 - Variability in surface mineralogy leads to localized pitting
- Local features are not predicted by the batch model or 1D reactive transport models but may play important role in fracture evolution.

0.5 mm




July 18, 2006

Marriott Hotel
Golden, CO



Results/Accomplishments




- Flow simulations in the measured aperture fields demonstrate enhanced channeling caused by dissolution.
- Despite 40% increase in measured mean aperture, simulations predict negligible change in hydraulic aperture.
- Remaining discrepancy between measured and simulated permeabilities likely due to measurement error and depth-averaging assumptions.
- Predicting long-term evolution of fracture reservoir permeabilities will require incorporating constitutive relationships that can effectively represent the role of localized mechanisms.

July 18, 2006

Marriott Hotel
Golden, CO



Results/Accomplishments




July 18, 2006

- Adequately representing the influence of flow channeling on dissolution / precipitation processes requires 2D reactive transport modeling.
- Ongoing efforts involve solving 1D reactive transport along evolving streamtubes predicted by the flow model.
- This effort leverages current LLNL research (BES, LDRD) on coupled reactive transport / mechanical deformation in variable aperture fractures.
- Recent development of parallelized discrete fracture network reactive transport model will allow us to extrapolate experimental results to larger scales.

Marriott Hotel
Golden, CO

Results/Accomplishments



- Thermal stress experiments are ongoing.
- Injection of cold water leads to a rapid drop in effluent temperature.
- Moderate increase in permeability observed for this test.
- Future experiments aimed at evaluating the relative magnitude of permeability alterations due to thermal effects and geochemical effects.



Conclusion

- Ongoing experiments provide a controlled data set for evaluating scalable computational models of chemical / mechanical mechanisms that lead to fracture alteration and meet our FY06 objectives.
- Recently initiated thermal stress experiments (FY07 objectives) will provide comparison between thermal effects and previously measured geochemical effects.
- We are developing mechanistic models that will allow us to extend results to a broader range of parameter space than is experimentally feasible.
- These efforts will lead to currently unavailable constitutive relationships for these coupled processes in fractured rocks that can be incorporated into large scale reservoir models.